



*Single direction only with
Compact Tractor Power Pack

Quick Power Scape™

Power Tiller / Leveler / Soil Conditioner

FEATURES

- Our universal quick attach plates fit most skid steers
- Direct-drive motor turns large 10" rotor
- Tungsten – carbide teeth
- Power angling (optional)
- Large solid rubber wheels



Till, Level, and Condition...

Our Soil Conditioner is an attachment that pays for itself in a very short amount of time by replacing your hand labor work crew. This versatile unit rakes stones and debris to either side or straight ahead for easy pickup. The aggressive teeth on the large-diameter rotor pulverize soil like an ordinary tiller, with the benefit of faster ground speed. The counter-rotating rotor moves soil ahead of it as it tills, filling in low spots and chewing off high spots. It creates perfect seedbeds and windrows. The Quick Power Scape separates rocks, tears up sod, and pulverizes dirt clods. We rake and till deeper than any of our competitors – as deep as 4".



Larger 10" rotor moves a higher volume of dirt than the competition.

Prices and specifications subject to change without notice.



1-866-428-8224

www.quickattach.com



F.O.B. THE FACTORY



SKID STEER

MINI SKID STEER

COMPACT TRACTOR

UTV

Quick Power Scope

72" Model - #900534

84" Model - #900536



Floating connection provides automatic leveling that follows the contour of the ground



Optional: Pistol Grip Control Harness is required if skid steer is **NOT** equipped with attachment control system. (Only needed when ordering hydraulic angling model).

Optional: Wire harness for hydraulic models with attachment controls. Fits Cat/ASV (8-pin) and John Deere/New Holland/CASE/Bobcat (14-pin)

Direct drive motor gives higher production with lower maintenance

Large solid rubber tires allow easier maneuverability over rough terrain

FAT-N | Char-Lynn

AVAILABLE OPTIONS

- 72" Model
- 84" Model
- Hydraulic Power Angling
- Pistol Grip Control Harness
- Loader Specific Wire Harness (for hydraulic model only)
- Factory Installed Faster Flat-Faced Couplers
- Factory Installed Parker Flat-Faced Couplers

STANDARD SPECIFICATIONS

Model	FSC72	FSC84
Rotor Width	72"	84"
Overall Width	79.5"	91.5"
Angling	manual 25°	manual 25°
Hydraulic Angling	optional	optional
Wheels/Tires	18 x 8.50 Polyurethane	18 x 8.50 Polyurethane
Teeth	88 Carbide Tipped	104 Carbide Tipped
Recommended Hyd. Flow	15 – 33 GPM	15 – 33 GPM
Mounting Plate	universal	universal
Operating Weight	1150#	1250#



"Christ will make His home in your hearts as you trust in him." Ephesians 3:17

Phones open 24 hours a day, 7 days a week...